

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) A power distribution system comprising:
at least one or more loads, each of the ~~at least one~~ load operable to be mounted in a rack location;
a plurality of power sources, each power source having a capacity less than each load and operable to be mounted in a rack location not having a load; and
an interconnect arrangement including a plurality of interconnects, the interconnects connecting each of the ~~at least one~~ load to a given number of the sources so that each of the ~~at least one~~ load is fully powered and if any one source fails, all loads of the ~~at least one~~ each load remains fully powered.
2. (Original) The power distribution system of claim 1 wherein all of the sources are DC sources.
3. (Original) The power distribution system of claim 1 wherein all of the sources are AC sources.
4. Canceled.
5. Canceled.
6. (Currently Amended) The power distribution system of claim 1 wherein the ~~at least one~~ or more loads, the plurality of power sources and the interconnect arrangement together comprise a power distribution subsystem, wherein the ~~at least one~~ or more loads includes a 4X watt load, wherein the plurality of sources include first, second, and third 2X watt sources, and wherein the interconnect arrangement includes interconnects that connect the 4X watt load to each of the first, second, and third 2X watt sources, X having a numeric value.

7. (Currently Amended) The power distribution system of claim 1 wherein the at least one or more loads, the plurality of power sources and the interconnect arrangement together comprise a power distribution subsystem, wherein the at least one or more loads includes a 5X watt load, wherein the plurality of sources include first, second, third, fourth, fifth, and sixth 2X watt sources, and wherein the interconnect arrangement includes interconnects that connect the 5X watt load to each of the first, second, third, fourth, fifth, and sixth 2X watt sources, X having a numeric value.

8. (Currently Amended) The power distribution system of claim 1 wherein the at least one or more loads includes a 10X watt load, wherein the plurality of sources include first, second, third, fourth, fifth, and sixth 2X watt sources, and wherein the interconnect arrangement includes interconnects that connect the 10X watt load to each of the first, second, third, fourth, fifth, and sixth 2X watt sources, X having a numeric value.

9. Canceled.

10. Canceled.

11. Canceled.

12. (Currently Amended) The power distribution system of claim 1 wherein the at least one or more loads includes an 8X watt load, wherein the plurality of sources include first, second, and third 4X watt sources, and wherein the interconnect arrangement includes interconnects that connect the 8X watt load to each of the first, second, and third 4X watt sources, and wherein the interconnect arrangement includes interconnects that connect the 8X watt load to each of the first, second, and third 4X watt sources, X having a numeric value.

13. (Currently Amended) A power distribution system comprising:
a plurality of loads, each load operable to be mounted in a rack location;
a plurality of power sources, the power sources having a collective capacity to fully power all of the loads and each power source having a capacity less than each load and operable to be mounted in a rack location not having a load; and

an interconnect arrangement including a plurality of interconnects, the interconnects connecting each load to a given number of different ones of the sources so that each load is fully powered notwithstanding failure of any one of the sources.

14. (Currently Amended) A method of distributing full power to each one of a plurality of loads, each load operable to be mounted in a rack location, the method comprising:

providing a plurality of power sources, each power source having a capacity less than each load and operable to be mounted in a rack location not having a load, the power sources being sufficient in number and capacity such that a combination of less than all of the sources is sufficient to power each load; and

connecting each load to a given number of the sources so that if any one source fails, each of the loads remains fully powered.

15. (New) The power distribution system of claim 1 wherein the one or more loads include first and second 5X watt loads, wherein the plurality of sources include first, second, third, fourth, fifth, and sixth 2X watt sources, and wherein the interconnect arrangement includes interconnects that connect the first 5X watt load to each of the first, second, third, fourth, fifth, and sixth 2X watt sources and the second 5X watt load to each of the first, second, third, fourth, fifth, and sixth 2X watt sources, X having a numeric value.

16. (New) The power distribution system of claim 1 wherein the number of sources is three-times the number of loads.

17. (New) The power distribution system of claim 1 wherein the number of sources is six-times the number of loads.